

## 20 Volt Lithium-Ion Grease Gun

Built-in Intelligence

ALEMITE

NOS MC



LCD with real-time information:

- Grease meter
- Grease level gauge
- Battery capacity gauge

Two flow rates:

- High 6 oz/min (170 g/min)
- Low 4 oz/min (113 g/min)

15 grease cartridges per battery charge





#### **Durable & Efficient**

- Ball and needle bearings
- Curved slot yoke optimizes mechanical efficiency
- Case-hardened piston for wear and bend resistance
- Impact-resistant LCD lens surrounded by impactabsorbing bezel

• LED flashlight with on/off control

Convenient



#### Patented Airflow Management

• Optimizes motor and transmission life

#### Ergonomic

ALEMITE®

- Shape, weight and balance designed for less physical strain
- Soft, comfortable grip



### **Multi-function LCD**

# LCD and Icons Keep You in Control

 Button resets functions, turns flashlight on or off and toggles between ounces and grams



Switch allows you to choose between two flow rates



Display turns red during stall condition



Display flashes red when the gun loses prime or runs out of grease



Battery level flashes to signify low voltage



Grease level flashes when low grease condition occurs



Precise Lubrication – Built-in Intelligence – Only from the Lubrication Specialists



### **Specifications**

| Model<br>Number | Li-Ion Battery |         |      | 70-minute   | Durante                 | Flow Rate               |                         | Cartridges per<br>Battery Charge |              | Weight             |
|-----------------|----------------|---------|------|-------------|-------------------------|-------------------------|-------------------------|----------------------------------|--------------|--------------------|
|                 | Quantity       | Voltage | mAh  | Charger     | Pressure                | High                    | Low                     | High<br>Speed                    | Low<br>Speed | weight             |
| 596-A           | 1              | - 20 V* | 1500 | 110 V/60 Hz | 10,000 psi<br>(690 bar) | 6 oz/min<br>(170 g/min) | 4 oz/min<br>(113 g/min) | 13                               | 15           | 6.3 lb<br>(2.9 kg) |
| 596-B           | 2              |         |      |             |                         |                         |                         |                                  |              |                    |
| 596-C           | 1              |         |      | 220 V/50 Hz |                         |                         |                         |                                  |              |                    |
| 596-D           | 2              |         |      |             |                         |                         |                         |                                  |              |                    |

\*Maximum initial voltage without workload

### Accessories

| Mobile<br>Charger | Carrying<br>Strap | 20 V Li-Ion Battery | Pressure<br>Relief<br>Valve | Bulk<br>Loader<br>Fitting |  |
|-------------------|-------------------|---------------------|-----------------------------|---------------------------|--|
| 343289            | 339812            | 343291              | 340338                      | 322610                    |  |



1057 Red Ventures Drive Suite 100 Fort Mill, SC 29707 Toll Free U.S.: 866-4-Alemite Toll Free Canada: 800-267-8022 International: 803-802-0001 Fax U.S.: 800-648-3917 Fax Canada: 800-267-2880 Fax International: 803-802-0192 www.alemite.com

Alemite<sup>®</sup> is a registered trademark of Alemite LLC

Precise Lubrication – Built-in Intelligence – Only from the Lubrication Specialists